EB016-017

# EUROSCHOOL MINIBASKET WITH ANCHORAGE, OVERHANG 1.00m BASKET HOOP



# Data sheet index

•	E	UROSCHOOL MINIBASKET WITH ANCHORAGE BASKET HOOP.	2
		Structure and anchorage to the ground.	
	0	Frame stabilization system and basket hoop frame.	4
	0	Materials.	4



In order to constantly improve the quality of our products, Euronix reserves the right to modify any of the technical characteristics.

EURONIX METAL, S.L.



### EUROSCHOOL MINIBASKET WITH ANCHORAGE, OVERHANG 1.00m BASKET HOOP



# EUROSCHOOL MINIBASKET WITH ANCHORAGE BASKET HOOP.

The **EUROSCHOOL MINIBASKET WITH ANCHORAGE** basket hoops which have a 1,00 meters cantilever, are made according to the guideline, and are designed to be able to install in whatever exterior surface.

They are made fundamentally of:

- Structure and anchorage to the ground.
- The frame stabilization system and basket hoop frame.

In order to constantly improve the quality of our products, Euronix reserves the right to modify any of the technical characteristics.

EURONIX METAL, S.L.

# EB016-017


### EUROSCHOOL MINIBASKET WITH ANCHORAGE, OVERHANG 1.00m BASKET HOOP



### o Structure and anchorage to the ground.

It's made of two 100x100x3 square profiles. The arm is joined to the foot by a screwed joint, through a Steel conformed "U" that fastens to the foot on all three sides of the profile: thus allowing the regulation in height and increasing the resistance of the joint.

The foot of the basket hoop is fixed by a plate and 4 reinforcement squares. The plate is screwed to the anchorage provided by Euronix, on this way the equipment acquires a totally fixation, stability, and rigidity.



In order to constantly improve the quality of our products, Euronix reserves the right to modify any of the technical characteristics.

EURONIX METAL, S.L.

# EB016-017

### EUROSCHOOL MINIBASKET WITH ANCHORAGE, OVERHANG 1.00m BASKET HOOP



## • Frame stabilization system and basket hoop frame.

The basket frame is fully established by two stiffeners made of a pair of adjustable tubes that joins the structure with the frame, guaranteeing 100% the straightness of the board, obtaining the desired perpendicularity with respect to the ground.

In addition, the basket frame is 1200mmx900mm according to the guideline and it is joined to the basket arm through a screwed joint.


The frame has two angles welded at the back ensuring the resistance of the equipment, and at the front the rim and the net fully normalized.

# Element Specification Profiles / Plates / Frame \$235 JR y \$275 JR Steel Screws Zinc (Zn) Quality 8.8 Net Natural or synthetic fiber

In order to constantly improve the quality of our products, Euronix reserves the right to modify any of the technical characteristics.

• Materials.

EURONIX METAL, S.L.



Ref.	Finish	Dimensions (m)	Weight (Kg.)
	Galvanized	1 bag of 2,75x0,325x0,325	40
EB016		1 bag of 1,00x0,30x0,30	40
		1 bag of 1,20x0,90x0,20	+/-32 Depending on the panel
	100% Polyester painted	1 bag of 2,75x0,325x0,325	40
EB017		1 bag of 1,00x0,30x0,30	40
		1 bag of 1,20x0,90x0,20	+/-32 Depending on the panel

In order to constantly improve the quality of our products, Euronix reserves the right to modify any of the technical characteristics.

EURONIX METAL, S.L.